

## Instructions for use

Jacket art. 2-1512-016	Trousers art. 2-5694-016
Jacket art. 2-3511-016	Trousers art. 2-5892-016
Jacket art. 2-3694-016	Trousers art. 2-5893-016
Coat art. 2-4892-016	Bib-trousers art. 2-6511-016
Coat art. 2-4893-016	

### Intended use

Protective clothing, anti-electrostatic, protecting against liquid chemicals, consists of jackets, coats, trousers and bib-trousers indicated above. Clothing designed for use in explosive atmosphere where the static electricity may cause ignition and in case of splash, protects against liquid chemicals (Typ PB [6] - table 1). Clothing meets the essential requirements for personal protective equipment contained in the Regulation of the European Parliament and of the EU Council 2016/425 of 9 March 2016 on personal protective equipment and in the standards: EN ISO 13688:2013; EN 1149-5:2018, EN 13034:2005+A1:2009.

### Use

Clothing should be used only in set: jacket or coat with trousers or bib-trousers indicated above or others meeting the same standards. Clothing should always be buttoned during use. For proper protection against static electricity, the user should be properly grounded. The electrical resistance between the human skin and the ground should be less than 108Ω, e.g. by wearing appropriate footwear on distracting or conductive floors. Clothing should not be unzipped and / or removed in flammable or explosive atmospheres and when handling flammable or explosive substances. Clothing is intended to be worn in Zones 1, 2, 20, 21 and 22 in which the minimum ignition energy of each explosive atmosphere is not less than 0.016 mJ. Clothing should not be used in oxygen enriched atmospheres and Zones without the prior approval of the safety engineer. Clothing during normal use (including bending) should completely cover all materials that do not meet the requirements of EN 1149-5:2018. When using clothing, acid or alkaline sprayed areas should be immediately flushed with a water. For proper protection, it is recommended to use additional personal protective equipment, e.g. protective gloves, eye and face protection equipment.

### Storage and transport


The clothing should be transport in original packaging (plastic bags), protecting against dirt, mechanical damage and getting wet. Store the clothing in a dry and well-ventilated place, away from heat sources. Do not store the clothing when it is dirty.

### Repair

Each time before use, an employee intending to use clothing should inspect the clothing for damage. Clothing can only be repaired by the manufacturer or specialized facilities. Damaged items of clothing (pleats, flaps, front parts or sleeves) should be replaced. Fabrics and threads as well as missing fasteners (buttons, adhesive tapes) used for repairs should be original, supplied by the clothing manufacturer. Clothing after repair should keep its original shapes and dimensions. ATTENTION: A faulty repair can result in the loss of protective properties of clothing.

### Body dimensions to the size of protective clothing

In order to properly choose the size of clothing, use the information in the size table. Body measurements should be made at the places marked in the figure below.

Sizes for men's clothing					Sizes for women's clothing			
Size	Height (A)	Chest size (B)	Waist size (C)		Size	Height (A)	Chest size (B)	Hip size (D)
46	164-170	88-92	80-84		34	158-164	76-80	88-92
48	170-176	92-96	84-88		36	158-164	80-84	88-92
50	170-176	96-100	88-92		38	158-164	84-88	92-96
52	176-182	100-104	92-96		40	164-170	88-92	96-100
54	176-182	104-108	96-104		42	164-170	92-96	100-104
56	182-188	108-112	104-108		44	170-176	96-100	104-108
58	182-188	112-116	108-116		46	170-176	100-104	108-112
60	188-194	116-120	116-120		48	170-176	104-112	112-116
62	188-194	120-124	120-128		50	176-182	112-116	116-120
					52	176-182	116-124	120-128

### Additional information

- The properties of clothing, resulting from the requirements of EN 1149-5:2018 (EN 1149-3 method), confirmed after 50 maintenance cycles.
- The effectiveness of the protection provided by clothing can be affected by: wear, damage, washing and possible contamination.
- Partial body protection Type PB [6] - clothing has not been tested according to the complete clothing test (item 5.2 EN 13034:2005 +A1: 2009).
- In order to maintain protection against liquid chemicals, it is recommended to re-apply the finish after each maintenance cycle using impregnation agents, ie: Kreussler Hydrob-FC; BurnusHyChem Hydro-Stop; EcoLab Saprit Protect Plus. If a different agent is needed, prior contact with the clothing manufacturer is required.
- The personal protection equipment after use is a waste, which the user should properly classify and then transfer for disposal in accordance with applicable law.
- No allergenic substances have been found in the materials used to manufacture the clothing; however, if any allergic reactions are noticed, especially in the case of sensitive individuals, such a person should leave the working zone, take off the garment and consult a doctor.
- It is advisable to keep this manual for further reference.

EU Type Examination Certificate No. **06/2020/PPE/1435** issued by notified body no. **Nr 1435 – Sieć Badawcza Łukasiewicz - Instytut Włókiennictwa**, ul. Brzezińska 5/15, 91-103 Łódź.

EU Declaration of Conformity at: [www.kegel.pl/ce](http://www.kegel.pl/ce)

Composition: Fabric: Polyester 65%, Cotton 34%, Antistatic fiber 1%










 <p><b>EN 13034:2005+A1:2009 Typ PB [6]</b></p>	 <p><b>EN 1149-5:2018</b></p>	 <p><b>CE 1435</b></p>	
Protection against accidental, small splashing of chemicals with low volume pressure, against which a complete liquid penetration barrier (at the molecular level) is not required. Type PB [6] - partial body protection	Protection against static electricity	Clothing meets the essential requirements for personal protective equipment, contained in the Regulation (UE) 2016/425. The PPE is subject to the conformity assessment procedure to type based on internal production control plus supervised product check at random intervals (Module C2) under surveillance of notify body no. 1435.	Before using, read the contents of this instructions for use.

Table 1

Usage requirements	Test results	Usage requirements	Test results
<b>Abrasion resistance</b>	Class 6	<b>Tear resistance</b>	Class 3
<b>Tensile strength</b>	Class 5	<b>Puncture resistance</b>	Class 3
<b>Repellency to liquids:</b>		<b>Resistance to penetration by liquids:</b>	
H <sub>2</sub> SO <sub>4</sub> 30 %	Class 3	H <sub>2</sub> SO <sub>4</sub> 30 %	Class 3
NaOH 10%	Class 3	NaOH 10%	Class 3
o-ksylen	Class 3	o-ksylen	Class 2
butan-1-ol (undiluted)	Class 2	butan-1-ol (undiluted)	Class 3

### Maintenance

Do not wash clothing with other clothing. Use the following maintenance procedures:

				
Maximum washing temp. 60°C - normal process	Do not bleach	Tumble drying possible - lower temperature. Max. exhaust temp. 60°C	Iron at max. sole-plate temperature of 150°C	Professional dry cleaning in tetrachloroethene and all solvent listed for the symbol F, normal process